

Rotary Professional

YAPI32Y

caulking guns

Technical Data Sheet

Rotary Professional Gun for caulking. This gun has a rotary skeleton body, that helps to the application of the material in places of difficult access. Solid construction for professional use. The combination of thrust ration (14:1) and its smooth bar; makes that the application is soft and constant, ideal for low medium and high viscosity products, mainly polyurethane and hybrid sealants, architectural degree silicone and adhesives.

Technical Information

| PROPERTIES | VALUE |
|------------------|--------------------------------|
| Series | Premium |
| Size | Cartridge up to 300 ml. |
| Construction | High metallurgic density block |
| Plunger | Hardened smooth iron of 10 mm |
| Grip and trigger | Black aluminum |
| Pressure power | 4500 Newton |
| Thrust ratio | 14:1 |
| Anti-drip | Yes |
| Unitary weight | 1,6 Pounds |
| Unit dimensions | 13.5 x 2 x 8.5 pounds |
| Quantity per box | 6 units |

Information obtained from laboratory tests.

Technical Support

Productos Pennsylvania's Technical Support is at your service, assisting you with:

Guidance in how to apply this or any of our products.

Blueprint reviews.

Joint dimension calculus.

Compatibility and adhesion testing of our sealants with different materials.

Technical Support: 800 90 210 00 soporte.tecnico@pennsylvania.com.mx

Uses

- Professional use for cartridge up to 300 ml.
- Ideal for polyurethane sealants, hybrids, architectural degree silicones and adhesives.



NOTE

Productos Pennsylvania S.A de C.V. provides technical assistance when required. Please contact our Technical Department regarding use and application of this product. It is the user's responsibility to test the product and its uses before application.

Productos Pennsylvania, S.A. de C.V. Camino a San José 1, Fracc. San Pablo Tecnológico, C.P. 76150, Querétaro, Qro. México

